

PVC-U Beads

An alternative range of impact resistant drylining & wet plaster beads for internal or external use.

PVC Plaster Beads are designed for use externally where galvanised beads cannot be used or where they are preferred to stainless steel. They are also used internally in high moisture content areas or where pro-longed drying out periods may be necessary.

Other benefits include:

- Simple installation (with plaster dabs or stainless steel fixings)
- No sharp edges, and safe to handle
- Easy to cut (by use of tin snips or fine tooth saw)
- Non corrosive.

PVC Bead is supplied as standard in white, although many colours are available upon request by supplying us with the relevant 'RAL' reference code.

PVC-U Movement Bead

Description and Application

PVC-U Movement Bead is used to overcome movement tolerances in plaster and render finishes thus minimising cracking in finished coat. It can also be used to act as a stop barrier for when a change in finish is required or type of render finish.

Different sizes available for various plaster / render thickness.



PVC-U Movement Bead is available in 2.5m lengths with 25 lengths per carton.

Code	Description	Length (m)	Size (mm)
TLP06MB25	PVC-U Movement Bead	2.5	6
TLP10MB25	PVC-U Movement Bead	2.5	10
TLP15MB25	PVC-U Movement Bead	2.5	15
TLP20MB25	PVC-U Movement Bead	2.5	20

All PVC Beads are available in alternative colours, namely; black, grey, ivory, terracotta and brown as shown here.

